



DETAIL B (B)

Single/Dual carriageway 40mph or less - 450mm traffic cones, spacing 1.5m.
 Single/Dual carriageway 50mph or more - 750mm traffic cones, spacing 1.5m.
 Dual carriageway national speed limit - 750mm traffic cones, spacing 1.5m, relaxation 3m.

Notes:
 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
 2) 45° tapers have 1.5m spacing, no relaxations.
 3) On motorways and NSL AP duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

SAFETY ZONE DIMENSIONS (S)	
Permanent speed limit 30mph or less	
Sideways safety zone	0.5m
Longways safety zone	0.5m
(Dimensions are minima)	

KEY	
	Traffic sign
	Traffic cone
	No Parking Cone
	Traffic signals to Diagram 3000.1
	Closure area
	Parking Suspended
	Pedestrian Barrier

QTY: 3	REF: 7011.1	
3 Way Control - Wait here until green light shows		
QTY: 3	REF: 543	
Traffic signals ahead		
QTY: 3	REF: 7001	
Road works ahead		
QTY: 1	REF: 517	
Road narrows on one side only ahead		
QTY: 2	REF: 518	
Single file traffic		
QTY: 2	REF: 513-2	
Max Speed		
QTY: 2	REF: 610	
Keep right		
QTY: 1	REF: 7105	
Lane closure barrier		
QTY: 1	REF: 517	
Road narrows on one side only ahead (variant)		
QTY: 1	REF: 610	
Keep left		

Watling Streetworks Limited
 2 Premier Road
 Ramsey, Isle of Man IM8 3AS
 Telephone: 07624 495166
 Email: Doug@watlingstreetworks.com

3 Way PTS Setup
 Railway Line Works
 Traffic Management Plan
 Client: SCUk

Drawn By	Amendment	Date	Traffic Management By
DKW	Proposed	28.11.19	

DRG Ref: 1172
 Area/ Road: Groudle
 SCALE : Not to Scale DIMENSIONS : Meters
 Reproduced from the Isle of Man Survey Map with the permission of the Department of Infrastructure
 Original drawing size A1 © Crown Copyright