



DETAIL B (B)

Single/Dual carriageway 40mph or less - 450mm traffic cones, spacing 1.5m.
 Single/Dual carriageway 50mph or more - 750mm traffic cones, spacing 1.5m.
 Dual carriageway national speed limit - 750mm traffic cones, spacing 1.5m, relaxation 3m.

Notes:
 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
 2) 45° tapers have 1.5m spacing, no relaxations.
 3) On motorways and NSL AP duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

SAFETY ZONE DIMENSIONS (S)
 Permanent speed limit 30mph or less
 Sideways safety zone 0.5m
 Longways safety zone 0.5m
 (Dimensions are minima)

KEY

- Traffic sign
- Traffic cone

QTY: 2 REF: 7001 Road works ahead 900mm High	
QTY: 1 REF: 572 Distance ahead to hazard (variant) 100 x-height	
QTY: 2 REF: 7011 When Red Light Shows Wait Here 750mm High	
QTY: 1 REF: 517 Road narrows on one side only ahead 900mm High	
QTY: 2 REF: 543 Traffic signals ahead 900mm High	
QTY: 2 REF: 518 Single file traffic 100 x-height	
QTY: 2 REF: 513-2 Max Speed 75 x-height	
QTY: 3 REF: 7021 Advance warning of PTS control on main road ahead 750mm High	
QTY: 3 REF: 610 Keep /right 900mm Dia	
QTY: 1 REF: 7105 Lane closure barrier 300mm High	
QTY: 1 REF: 517 Road narrows on one side only ahead (variant) 900mm High	
QTY: 1 REF: 572 Distance ahead to hazard (variant) 100 x-height	
QTY: 1 REF: 610 Keep left 900mm Dia	

Watling Streetworks
 2 Premier Road
 Ramsey, Isle of Man IM8 3AS
 Telephone: 07624 495166
 Email: Doug@watlingstreetworks.com

Drainage Repairs
 Rhencullen
 2 Way PTS
 Client: DoI

Drawn By: DKW
 Amendment: Proposed
 Date: 15.11.19

Traffic Management By

DRG Ref: 1172
 Area/ Road: Rhencullen
 SCALE : Not to Scale DIMENSIONS : Metres
 Reproduced from the Isle of Man Survey Map with the permission of the Department of Infrastructure
 Original drawing size A1 © Crown Copyright